



## PU FLEX NYLON (70 MICRON)




White  
S100




Black  
S199



Navy Blu  
S205



Royal Blu  
S230



Red  
S350



Orange  
S370




Gold Yellow  
S410



Medium Yellow  
S430




Green  
S540



Forest Green  
S560



Silver  
M150



Gold  
M410

# PU FLEX

## DESCRIPTION

Material for laser and plotter cutting applications

## ÜRÜN TANIMI

Lazer ve plotter ile kesim uygulamaları için malzeme

## SPECIFICATION

**Size:** 50 cm x 25 m

**N.W:** 5 kg / roll

## ÖZELLİKLER

**Ebat:** 50 cm x 25 m

**Net kilo:** 5 kg / rol

## TRANSFER CONDITION

The following instructions are given as guideline only.

**Temperature:** 150°C (302°F)

**Pressing time:** 12 seconds

## BASIM TALİMATLARI

Aşağıdaki talimatlar sadece normal şartlara göredir.

**Derece:** 150°C (302°F)

**Baskı süresi:** 12 saniye

## SUITABLE FOR

Cotton, mixtures of polyester / cotton and polyester / acrylic or for similar textile.

Not suitable for treated and dyed garments.

## UYGUN KUMAŞLAR

Pamuk, polyester / pamuk karışımı, polyester / akrilik vb tekstiller için uygundur.

Boyanmış ve işlem görmüş kumaşlar için uygun değildir.

## NOTICE

We offer you to test the product against the color migration.


Pressing instruction may change, according to the fabric type.

## UYARI

Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.



Out the image in reverse  
Deseni tersten kesiniz




160°C (320°F)  
160°C (320°F)




4 Bar pressure  
4 Bar basınç



12 seconds for pressing  
12 saniye presleme



COOL Peel  
Soğuk çekim



45°



After 24H with Application  
Uygulamadan 24 saat sonra