


**HOLOGRAM (100 MICRON)**




H-01  
Silver




H-02  
Gold




H-03  
Fuchsia



H-04  
Pink




H-05  
Red



H-06  
R/Blue




H-07  
Violet




H-08  
Green




H-09  
Purple




H-10  
Black




H-11  
Sky




H-12  
Orange



H-13  
Aqua



H-14  
L/Green



H-15  
Brown




H-16  
S/Silver



H-17  
Rainbow(A)



H-18  
Rainbow(B)




CR  
Crystal




CRG-G  
Crystal

**SOLID FOIL (100 MICRON)**



N-01  
Silver




N-02  
Gold




N-03  
Fuchsia



N-04  
Pink



N-05  
Red



N-06  
R/Blue



N-07  
Violet



N-08  
Green




N-09  
Sky



N-10  
Black




N-11  
Clear




N-12  
Orange



N-13  
Aqua




N-14  
L/Green




N-15  
Copper



N-16  
Mint



N-17  
L/Brown




N-18  
Grey



N-19  
M/Silver



N-20  
Rainbow



N-21  
White

# HOLOGRAM / SOLID FOIL

## DESCRIPTION

Material for laser and plotter cutting applications

## SPECIFICATION

Size: 50 cm x 100 m  
N.W: 14 kg / roll

## TRANSFER CONDITION

The following instructions are given as guideline only.  
Temperature: 160°C (320°F)  
Pressing Time: 12 seconds

## SUITABLE FOR

Cotton, mixtures of polyester / cotton and polyester / acrylic or for similar textile.  
Not suitable for treated and dyed garments.

## NOTICE

We offer you to test the product against the color migration.  
Pressing instruction may change, according to the fabric type.

## ÜRÜN TANIMI

Lazer ve plotter kesim uygulamaları için malzeme

## ÖZELLİKLER

Ebat: 50 cm x 100 m  
Net Ağırlık: 14 kg / roll

## BASKI TALİMATLARI

Aşağıdaki talimatlar sadece normal şartlara göredir.  
Derece: 160°C (320°F)  
Baskı Süresi: 12 saniye

## UYGUN KUMAŞLAR


Pamuk, polyester / pamuk karışımı, polyester / akrilik vb tekstiller için uygundur.  
Boyanmış ve işlem görmüş kumaşlar için uygun değildir.

## UYARI


Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.



Cut the image in reverse  
Deseni tersten kesiniz




160°C (320°F)




4 Bar pressure  
4 Bar basınç



12 seconds for pressing  
12 saniye presleme



COOL Peel  
Soğuk çekim



45°



After 24H with application  
Uygulamadan 24 saat sonra