


PU FLEX NYLON (70 MICRON)


S100
White




S199
Black




S205
Navy Blue




S230
Royal Blue




S350
Red




S370
Orange




S410
Gold Yellow



S430
Medium Yellow




S540
Green



S560
Forest Green



M410
Gold



M150
Silver

PU FLEX

DESCRIPTION

Material for laser and plotter cutting applications

SPECIFICATION

Size: 50 cm x 25 m

N.W: 5 kg / roll

TRANSFER CONDITION

The following instructions are given as guideline only.

Temperature: 150°C (302°F)

Pressing Time: 12 seconds

SUITABLE FOR

Cotton, mixtures of polyester / cotton and polyester / acrylic or for similar textile.

Not suitable for treated and dyed garments.

NOTICE

We offer you to test the product against the color migration. Pressing instruction may change, according to the fabric type.

ÜRÜN TANIMI

Lazer ve plotter kesim uygulamaları için malzeme

ÖZELLİKLER

Ebat: 50 cm x 25 m

Net Ağırlık: 5 kg / roll

BASKI TALİMATLARI

Aşağıdaki talimatlar sadece normal şartlara göredir.

Derece: 150°C (302°F)

Baskı Süresi: 12 saniye

UYGUN KUMAŞLAR

Pamuk, polyester / pamuk karışımı, polyester / akrilik vb tekstiller için uygundur.

Boyanmış ve işlem görmüş kumaşlar için uygun değildir.

UYARI


Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.



Cut the image in reverse
Deseni tersten kesiniz




150°C (302°F)




4 Bar pressure
4 Bar basınç



12 seconds for pressing
12 saniye presleme



COOL Peel
Soğuk çekim



45°



After 24H with application
Uygulamadan 24 saat sonra