









**CARBON FLEX (300 MICRON)**CS100  
WhiteCS199  
BlackCS320  
Royal BlueCS360  
Flame RedCS370  
OrangeCS385  
Baby PinkCS430  
Medium YellowCS520  
Apple GreenCSM150  
SilverCSM410  
GoldCSM600  
Graphite**NEW CARBON (550-600 MICRON)**

Gold



Silver

# CARBON FLEX / NEW CARBON

## DESCRIPTION

Material for laser cutting applications

## SPECIFICATION

### CARBON FLEX

Size: 50 cm x 20 m

N.W: 4,6 kg / roll

### NEW CARBON

Size: 50 cm x 50 m

N.W: 13,5 kg / roll

## TRANSFER CONDITION

The following instructions are given as guideline only.

### CARBON FLEX

Temperature: 160°C (320°F)

Pressing Time: 12 seconds

### NEW CARBON (Backside Press)

Temperature: 160°C - 165°C (320°F - 329°F)

Pressing Time: 12 seconds

## SUITABLE FOR

Cotton, mixtures of polyester / cotton and polyester / acrylic or for similar textile.

Not suitable for treated and dyed garments.

## NOTICE

We offer you to test the product against the color migration. Pressing instruction may change, according to the fabric type.

## ÜRÜN TANIMI

Lazer kesim uygulamaları için malzeme

## ÖZELLİKLER

### CARBON FLEX

Ebat: 50 cm x 20 m

Net Ağırlık: 4,6 kg / roll

### NEW CARBON

Ebat: 50 cm x 50 m

Net Ağırlık: 13,5 kg / roll

## BASKI TALİMATLARI

Aşağıdaki talimatlar sadece normal şartlara göre.

### CARBON FLEX

Derece: 160°C (320°F)

Baskı Süresi: 12 saniye

### NEW CARBON (Tersten Pres)

Derece: 160°C - 165°C (320°F - 329°F)

Baskı Süresi: 12 saniye

## UYGUN KUMAŞLAR

Pamuk, polyester / pamuk karışımı, polyester / akrilik vb tekstiller için uygundur.

Boyanmış ve işlem görmüş kumaşlar için uygun değildir.

## UYARI


Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.



Cut the image in reverse  
Deseni tersten kesiniz




160°C - 165°C  
(320°F - 329°F)



4 Bar pressure  
4 Bar basınç



12 seconds for pressing  
12 saniye presleme



COOL Peel  
Soğuk çekim



After 24H with application  
Uygulamadan 24 saat sonra