












PUFF PU (140±10 MICRON)PUFF 01
WhitePUFF 02
BlackPUFF 03
Royal BluePUFF 04
Navy BluePUFF 05
YellowPUFF 06
RedPUFF 07
Hot RedPUFF 08
OrangePUFF 09
GreenPUFF 10
GrayPUFF 11
Dark GrayPUFF 12
Golden YellowPUFF 13
PurplePUFF 14
PinkPUFF 15
Neon YellowPUFF 16
Neon OrangePUFF 17
Neon PinkPUFF 18
Neon GreenPUFF 19
Neon BluePUFF 20
Light Purple

PUFF PU

DESCRIPTION

It is suitable for laser and plotter cutting application. Puff Pu is pu film of puffed up effect. This film which is made of polyurethane gives a 3D effect when applied by heat.

SPECIFICATION

Size: 50 cm x 50 m
N.W: 8 kg / roll

TRANSFER CONDITION

The following instructions are given as guideline only.
Temperature: 165°C (329°F)
Pressing Time: 12 seconds

STORAGE CONDITION

Use the film within 1 year from manufacturing day.
It is recommended to stay away from direct sunlight, hot and humid place.

SUITABLE FOR

Cotton, mixtures of polyester / cotton and polyester / acrylic or for similar textile.
Not suitable for treated and dyed garments.

NOTICE

We offer you to test the product against the color migration.
Pressing instruction may change, according to the fabric type.

ÜRÜN TANIMI

Lazer ve plotter kesim için uygundur. Puff Pu, kabarık efektli pu filmidir. Poliüretandan yapılmış olan bu film, ısı uygulandığında 3D etkisi yaratır.

ÖZELLİKLER

Ebat: 50 cm x 50 m
Net Ağırlık: 8 kg / roll

BASKI TALİMATLARI

Aşağıdaki talimatlar sadece normal şartlara göre.
Derece: 165°C (329°F)
Baskı Süresi: 12 saniye

SAKLAMA TALİMATLARI

Film üretim gününden itibaren 1 yıl içinde kullanılmalıdır.
Direkt güneş ışığı, sıcak ve nemli ortamdan uzak tutulmalıdır.

UYGUN KUMAŞLAR

Pamuk, polyester / pamuk karışımı, polyester / akrilik vb tekstiller için uygundur.
Boyanmış ve işlem görmüş kumaşlar için uygun değildir.

UYARI


Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.



Cut the image in reverse
Deseni tersten kesiniz




165°C (329°F)




4 Bar pressure
4 Bar basınç



15 seconds for pressing
15 saniye presleme



HOT Peel
Sıcak çekim



45°



After 24H with application
Uygulamadan 24 saat sonra